



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/026,146	12/21/2001	Richard P. Volant	FIS920010219US1	8227
32074	7590	08/24/2004	EXAMINER	
INTERNATIONAL BUSINESS MACHINES CORPORATION DEPT. 18G BLDG. 300-482 2070 ROUTE 52 HOPEWELL JUNCTION, NY 12533			VU, HUNG K	
			ART UNIT	PAPER NUMBER
			2811	
DATE MAILED: 08/24/2004				

Please find below and/or attached an Office communication concerning this application or proceeding.

Office Action Summary	Application No. 10/026,146	Applicant(s) VOLANT ET AL.	
	Examiner Hung K. Vu	Art Unit 2811	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 10 June 2004.
- 2a) ☒ This action is **FINAL**. 2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-6 and 8-15 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-15 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
 Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
 Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. _____.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|---|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413) |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | Paper No(s)/Mail Date. _____ |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08) | 5) <input type="checkbox"/> Notice of Informal Patent Application (PTO-152) |
| Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

Claim Objections

1. Claim 9 is objected to because of the following informalities: In claim 9, line 7, after “by a” insert --distance-- for clarity. Appropriate correction is required.

Claim Rejections - 35 USC § 103

2. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

Claims 1, 4 and 5 are rejected under 35 U.S.C. 103(a) as being unpatentable over Zhao et al. (PN 5,861,647, of record) in view of Lin (PN 6,303,423).

Zhao et al. discloses, as shown in Figures 7 and 8, a passive electrical device comprising:

- a first electrical conductor (20);
- a second electrical conductor (52) disposed over the first electrical conductor;
- a third electrical conductor (48) connecting the first electrical conductor to the second electrical conductor, wherein the first, second and third electrical conductors are disposed on a semiconductor substrate (28,30) and wherein the sheet resistivity of the first electrical conductor is approximately equal to the sheet resistivity of the second electrical conductor. Note that the first and the second electrical conductors comprise the same material, it is inherent that the sheet resistivity of the first electrical conductor is approximately equal to that of the second electrical conductor [see Col. 3, lines 2-6 and 56-57];

wherein the third electrical conductor consists essentially of one substantially uniform chemical composition (tungsten, aluminum or copper) [see Col. 3, lines 40-41].

Zhao et al. discloses the third electrical conductor has a thickness which separates the first electrical conductor from the second electrical conductor by a distance in a range of 2.3 microns [see Col. 3, lines 23-27, note that the third electrical conductor 48 is formed in the dielectric layer 36 which is the combination of layers 38, 40 and 42]. Zhao et al. does not disclose the third electrical conductor has the thickness which separates the first electrical conductor from the second electrical conductor by a distance in a range of approximately three microns to approximately four microns. However, Lin discloses a device having a third electrical conductor (38) that has a thickness which separates a first electrical conductor (16) from a second electrical conductor (40) by a distance in a range of approximately three microns to approximately four microns. Note Figures 1, 2, 4, and Col. 8, line 52 – Col. 9, line 29, note that the third electrical conductor 38 is formed in the dielectric layers 18 and 20 having the thickness as claimed]. Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to form the third electrical conductor of Zhao et al. having a thickness, as taught by Lin in order to have a desired inductance according to electrical design requirements.

With regard to claim 4, Zhao et al. and Lin disclose the first, second and third electrical conductors consist essentially of copper [see Col. 3, lines 2-6, 39-43 and 56-57].

Art Unit: 2811

With regard to claim 5, Zhao et al. and Lin disclose the first and third electrical conductors consist essentially of copper, and the second electrical conductor consists essentially of aluminum [see Col. 3, lines 2-6, 39-43 and 56-57].

3. Claims 1-4, 6 and 9 are rejected under 35 U.S.C. 103(a) as being unpatentable over Wen et al. (PN 6,083,802, of record) in view of Lin (PN 6,303,423).

Wen et al. discloses, as shown in Figures 12 and 13, a passive electrical device comprising:

- a first electrical conductor (20);

- a second electrical conductor (28) disposed over the first electrical conductor;

- a third electrical conductor (26) connecting the first electrical conductor to the second electrical conductor, wherein the first, second and third electrical conductors are disposed on a semiconductor substrate (14) and wherein the sheet resistivity of the first electrical conductor is approximately equal to the sheet resistivity of the second electrical conductor. Note that the first and the second electrical conductors comprise the same material (copper), it is inherent that the sheet resistivity of the first electrical conductor is approximately equal to that of the second electrical conductor [see Col. 3, lines 5-14 and 53-65],

- wherein the third electrical conductor consists essentially of one substantially uniform chemical composition (tungsten, aluminum or copper) [see Col. 3, lines 55-57].

Wen et al. discloses the third electrical conductor has a thickness which separates the first electrical conductor from the second electrical conductor by a distance in a range of approximately 5 to 10 microns [see Col. 3, lines 39-41, note that the third electrical conductor 26 is formed in the dielectric layer 24]. Wen et al. does not disclose the third electrical conductor

Art Unit: 2811

has the thickness which separates the first electrical conductor from the second electrical conductor by a distance in a range of approximately three microns to approximately four microns. However, Lin discloses a device having a third electrical conductor (38) that has a thickness which separates a first electrical conductor (16) from a second electrical conductor (40) by a distance in a range of approximately three microns to approximately four microns. Note Figures 1, 2, 4, and Col. 8, line 52 – Col. 9, line 29, note that the third electrical conductor 38 is formed in the dielectric layers 18 and 20 having the thickness as claimed]. Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to form the third electrical conductor of Wen et al. having a thickness, as taught by Lin in order to have a desired inductance according to electrical design requirements.

With regard to claim 2, Wen et al. and Lin disclose each of the first, second and third electrical conductors has a respective thickness, and the thickness of the first electrical conductor is approximately equal to the thickness of the second electrical conductor [see Col. 3, lines 5-14 and 53-65].

With regard to claim 3, Wen et al. and Lin disclose each of the first, second and third electrical conductors has a respective thickness, and the thickness of the first conductor is approximately equal to the thickness of the second electrical conductor and being approximately one-half the thickness of the third electrical conductor.

Art Unit: 2811

With regard to claim 4, Wen et al. and Lin disclose the first, second and third electrical conductors consist essentially of copper [see Col. 3, lines 5-14 and 53-65].

With regard to claim 6, Wen et al. and Lin disclose each of the first and second electrical conductors has a respective thickness in a range of approximately five to 20 microns (within the range of approximately two to approximately 32 microns) [see Col. 3, lines 5-14 and 53-65].

With regard to claim 9, Wen et al., as shown in Figure 3 and 13, the inductor device comprising:

a semiconductor substrate (14);

first, second and third electrical conductors (24,26,28) provided on the substrate, wherein the first and second electrical conductors each has a thickness which is approximately equal [see Figures 3 and 13, Col. 3, lines 12-14 and 61-64],

wherein the third electrical conductor consists essentially of one substantially uniform chemical composition (tungsten, aluminum or copper) [see Col. 3, lines 55-57].

Wen et al. discloses the third electrical conductor has a thickness in a range of approximately 5 to 10 microns [see Col. 3, lines 39-41, note that the third electrical conductor 26 is formed in the dielectric layer 24]. Wen et al. does not disclose the third electrical conductor has the thickness which separates the first electrical conductor from the second electrical conductor by a distance in a range of approximately three microns to approximately four microns and the semiconductor substrate comprises silicon. However, Lin discloses a device having a third electrical conductor (38) that has a thickness which separates a first electrical conductor (16) from a second electrical conductor (40) by a distance in a range of approximately three microns to approximately four

Art Unit: 2811

microns and a semiconductor substrate (10) comprises silicon. Note Figures 1, 2, 4, and Col. 7, lines 28 – 29 and Col. 8, line 52 – Col. 9, line 29, note that the third electrical conductor 38 is formed in the dielectric layers 18 and 20 having the thickness as claimed. Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to form the third electrical conductor of Wen et al. having a thickness, as taught by Lin in order to have a desired inductance according to electrical design requirements, and to form the semiconductor substrate of Wen et al. comprising silicon because silicon is one of the materials that is commonly used to form the substrate.

4. Claims 5 and 8 are rejected under 35 U.S.C. 103(a) as being unpatentable over Wen et al. (PN 6,083,802, of record) in view of Lin (PN 6,303,423) and further in view of Zhao et al. (PN 5,861,647, of record).

With regard to claim 5, Wen et al. and Lin taught the invention substantially as claimed, including the passive electrical device as cited in the rejection of claim above. Wen et al. and Lin also taught the first, second and third electrical conductors consist essentially of copper. Wen et al. and Lin did not specifically teach the second electrical conductor consists essentially of aluminum. However, Zhao et al. taught a second electrically conductor (52) consists essentially of aluminum or copper [see Figures 8-9, Col. 3, lines 56-57]. Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to form the second electrical conductor of Wen et al. and Lin consists essentially of aluminum, such as taught by Zhao et al. because aluminum and copper are commonly used to form the conductor for they have lower resistance, and they are interchangeable.

With regard to claim 8, Wen et al., Lin and Zhao et al. disclose the second electrical conductor has a substantially uniform thickness in a range of approximately five to 20 microns (within the range of approximately four to approximately six microns) [see Col. 3, lines 5-14 and 53-65].

5. Claims 10-11 and 13-15 are rejected under 35 U.S.C. 103(a) as being unpatentable over Wen et al. (PN 6,083,802, of record) in view of Lin (PN 6,303,423) and further in view of Johnson et al. (PN 6,534,374, of record).

Wen et al. and Lin taught the invention substantially as claimed, including the passive electrical device as cited in the rejection of claim above. Wen et al. and Lin also taught the semiconductor substrate comprises silicon. Wen et al. and Lin did not teach the semiconductor substrate comprises silicon and germanium. However, Johnson et al. taught a semiconductor substrate (20) comprises silicon and germanium [see Figures 10 and 16 and Col. 5, lines 2-6]. Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to form the semiconductor substrate of Wen et al. and Lin comprising silicon and germanium such as taught by Johnson et al. since silicon and germanium are the materials that are commonly used to form the substrate.

With regard to claim 11, Wen et al., Lin and Johnson et al. taught the substrate comprises silicon on insulator substrate [see Col. 5, lines 2-6].

With regard to claim 13, Wen et al.; Lin and Johnson et al. taught the second electrical conductor is disposed over the first electric conductor [see Figures 8 and 13].

With regard to claim 14, Wen et al., Lin and Johnson et al. taught the first and second electrical conductors are spiral shaped [see Figure 2].

With regard to claim 15, Wen et al., Lin and Johnson et al. taught each of the first and the second electrical conductors has a sheet resistivity, the sheet resistivity of the first electrical conductor being approximately equal to the sheet resistivity of the second electrical conductor. Note that the first and the second conductors comprise the same material (copper), it is inherent that the sheet resistivity of the first conductor is approximately equal to that of the second conductor [see Col. 3, lines 5-14 and 53-65].

6. Claims 12, 13 and 15 are rejected under 35 U.S.C. 103(a) as being unpatentable over Wen et al. (PN 6,083,802, of record) in view of Lin (PN 6,303,423) and further in view of Ito (PN 4,758,896, of record).

Wen et al. and Lin taught the invention substantially as claimed, including the passive electrical device as cited in the rejection of claim above. Wen et al. and Lin also taught the semiconductor substrate comprises silicon. Wen et al. and Lin did not teach the semiconductor substrate comprises silicon and germanium. However, Ito taught a semiconductor substrate (10) comprises silicon-on-sapphire [see Figures 1 and 3 and Col. 8, lines 9-36]. Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to form

Art Unit: 2811

the semiconductor substrate of Wen et al. and Lin comprising silicon and germanium such as taught by Ito since silicon-on-sapphire are the materials that are commonly used to form the substrate.

With regard to claim 13, Wen et al., Lin and Ito taught the second electrical conductor is disposed over the first electric conductor [see Figures 8 and 13].

With regard to claim 15, Wen et al., Lin and Ito taught each of the first and the second electrical conductors has a sheet resistivity, the sheet resistivity of the first electrical conductor being approximately equal to the sheet resistivity of the second electrical conductor. Note that the first and the second conductors comprise the same material (copper), it is inherent that the sheet resistivity of the first conductor is approximately equal to that of the second conductor [see Col. 3, lines 5-14 and 53-65].

Response to Arguments

7. Applicant's arguments with respect to claims 1 and 9 have been considered but are moot in view of the new ground(s) of rejection.

Conclusion

8. Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP § 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the date of this final action.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Hung K. Vu whose telephone number is (571) 272-1666. The examiner can normally be reached on Mon-Thurs 6:00-3:30, alternate Friday 7:00-3:30, Eastern Time.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Eddie C. Lee can be reached on (571) 272-1732. The Central Fax Number for the organization where this application or proceeding is assigned is (703) 872-9306.

Any inquiry of a general nature or relating to the status of this application or proceeding should be directed to the receptionist whose telephone number is (703) 308-0956.

Vu

August 9, 2004



Hung Vu

Patent Examiner